


A case against WFIRST CGI polarization aberration compensation

John Krist
Jet Propulsion Laboratory, California Inst. of Technology
4 Dec 2018

Numerical Modeling

- Uses most recent testbed HLC design (HLC 20180925) for current WFIRST pupil
 - 10% bandpass centered at 575 nm
- Uses full system model with surface errors on each optic
- Uses polarization aberrations for Phase B TOMA computed by Jim McGuire using Code V
- EFC run for each polarization case
 - no polarization errors
 - X polarization
 - All polarizations
- No modelling uncertainty factors applied


HLC 20180925 (10%, λ_c =575 nm) Each result is after running EFC; no jitter




Circles are $r = 3 \& 10 \lambda/D$

	3 – 4 λ/D	4 – 9 λ/D
No pol errors	0.4 x 10 ⁻⁹	0.6 x 10 ⁻⁹
Single polarization	1.2 x 10 ⁻⁹	0.8 x 10 ⁻⁹
No polarizer	2.2 x 10 ⁻⁹	1.0 x 10 ⁻⁹


HLC 20180925 (10%, λ_c =575 nm) Each result is after running EFC; no jitter



HLC 20180925 (10%, λ_c =575 nm) Each result is after running EFC; with jitter



HLC 20180925 (10%, λ_c =575 nm) Each result is after running EFC; with jitter



Conclusions

- In the absence of any other factors, the difference in a polarizer-free system between perfectly-polarization-compensated contrast and uncompensated contrast is only significant out to $^{\sim}5~\lambda/D$ and is dependent on the unlikely ability to achieve as deep a contrast in real life as the models predict (not shown in the testbed)
- In the presences of other factors, notably jitter, the difference between these states quickly becomes negligible
- The application of modeling uncertainty factors does not alter these findings, since polarization aberration effects and jitter both would increase, and a significant uncertainty factor would need to be applied to the compensator
- The conclusion is that a polarization compensator in WFIRST CGI is not warranted